ether Research

SITE DESCRIPTION/EXECUTIVE SUMMARY

Site Name and Location

Cooper School 28611 Ann Arbor Trail Westland, MI 48185

US EPA RECORDS CENTER REGION 5



County: Wayne

82-02S-09E-01CB Michigan Code Number:

DNR District: Detroit

EPA ID Number: MID981189905

SAS Score/Screen No.: 02

The Cooper School site was an active municipal waste landfill from approximately 1925 to 1952. According to the Wayne County Health Department records, the types and amounts of municipal waste deposited in the landfill are unknown as well as its size.

The landfill, located on Cooper Elementary School property, is unfenced, and adjacent to a highly populated residential area and public park. The Rouge River, located approximately 800 feet from the site, flows through the park and lends itself to potential contamination through surface water runoff should the landfill be leaking.

The drinking water for residents within a three mile radius of the site is derived from Detroit's municipal water system, and is not threatened by the presence of the landfill.

No testing of water or soil has been conducted, and it is not known whether or not leachate from the landfill is present. The potential for such leachate is high as the site was active prior to Act 87, requiring the licensing of landfills.

Further research and preliminary water and soil testing is recommended as this landfill has the potential of endangering approximately four hundred children attending the school, as well as nearly 100,000 residents in the surrounding area.

Recommendations for EPA

This site receives a high priority for inspection	
Pre-HRS Score: To be determined	
Projected HRS Score: To be determined	
SI Priority: High - State lead	10-
Hours Spent: 10 + 15 + + +	= 1015
Initial & Date 11-17-87 SC 11/17/87	

Date of Previous Summary: Previous Author: Current Date: Author: Debra Spakoff

PASM 00631 TW

Site Assessment Unit Environmental Response Division Michigan Dept. of Natural Resources **SEPA**

POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT PART 1. SITE INFORMATION AND ASSESSMENT

1. IDENTIFICATION

01 STATE 02 SITE NUMBER

20 WID981189955

PART 1 - SITE INFORMA	TION AND ASSESSMENT
II. SITE NAME AND LOCATION	
31 SITE NAME (Legal, common, or descriptive name of site)	02 STREET, ROUTE NO., OR SPECIFIC LOCATION IDENTIFIER
Cooper School	28611 Ann Arbor Trail
west land	MI 18185 Wayne 183 15
12 20 45" 83 19 23"	Inkster Quad Mich-Wayne Co. 7.5 minute Series
From Lansing take I-96 East to Go South on Middlubilt approximat Turn luft (last) unto Ann Hobo-	
III. RESPONSIBLE PARTIES	
Wayne County (Livonia School District)	
Westland	04 STATE 05 ZIP CODE 06 TELEPHONE NUMBER
Dorcen Reid (Principal)	08 STREET (Quaness mailing, readense) 28611 Ann Arbor Tra:1
Wastland (Part of Luonia School Dist.)	10 STATE 11 ZIP CODE 12 TELEPHONE NUMBER WTL 48135 B131 523-9476
□ F. OTHER: (Specify)	C. STATE CD.COUNTY GE. MUNICIPAL
14 OWNER/OPERATOR NOTIFICATION ON FILE (Check at that apply) 2 A. RCRA 3001 DATE RECEIVED:	ED WASTE SITE CERCIA 103 41 DATE RECEIVED:
IV. CHARACTERIZATION OF POTENTIAL HAZARD	
OT ON SITE INSPECTION SY (Choose at intel aboly) A. EPA B. EPA NO MONTH DAY YEAR E. LOCAL HEALTH OFFI	CONTRACTOR C. STATE D. OTHER CONTRACTOR
CONTRACTOR NAME(S):	
02 SITE STATUS (Check only) 03 YEARS OF OPER! 03 A. ACTIVE [] B. INACTIVE [] C. UNKNOWN App. 7 X S	105)
104 DESCRIPTION OF SUBSTANCES POSSIBLY PRESENT, KNOWN, OR ALLEGED YOUN: C: Pal wastre	
Population: Direct Contacts The land	ter contamination. The landfill is located liker Soil Contamination
V. PRIORITY ASSESSMENT	The state of the s
01 PRIORITY FOR INSPECTION (Check one. If high or medium is checked, complete Part 2 - Wasse Infan	
☐ A. HIGH (Inspection reduced premarity) ☐ B. MEDIUM (Inspection reduced premarity) (Inspection reduced) (Inspection reduced)	D. NONE
VI. INFORMATION AVAILABLE FROM	
OF CONTACT Bib CaTZ La Cat Cat Cat Cat Cat Cat Cat Cat Cat Ca	
o ayric	OUNTY Hantch Dupt. (3.3) 526.4900
1 =	1517) 373-480 MONTH DAY YEAR

A	7-9	
771	}	
3~		4

POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT PART 2 - WASTE INFORMATION

I. IDENT	IFICA	TION		
OI STATE	O2 SITE	NUMBER	159	كدوء

	E. SLURRY	02 WASTE QUANT	TITY AT SITE of waste quentities independent	O3 WASTE CHARACT A TOXIC B CORRO GRADIOA D PERSIS	E SOL	UBLE HIGHLY CTIOUS EXPLO: MMABLE I REACT TABLE I NCOM	SIVE IVE
W 144 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	 	NO. UP UHUMS		<u> </u>			
CATEGORY			1				
SLU	SUBSTANCE NA	WE	01 GROSS AMOUNT	OZ UNIT OF MEASURE	03 COMMENTS		
OLW	OILY WASTE		 		 		
SOL	SOLVENTS			 	 		
PSO			UNKnown		 		
05C	PESTICIDES		 		11155 1.kg		
	OTHER ORGANIC CHE		Chi Kilocail		11105 1.kg	ty discost	
ACD	INORGANIC CHEMICA	L3	1, ,			- 	
	ACIDS		MAKMELINA	 			
BAS	BASES HEAVY METALS		Unitroun				
	US SUBSTANCES (See Appe				<u> </u>		
CATEGORY	OZ SUBSTANCE NAM		03 CAS NUMBER	04 STORAGE/DIS	POGAL METHOD	05 CONCENTRATION	06 MEASURE OF CONCENTRATION
// CATEGORY	02 3063 12402 1440		US GAS HOMBER	043104402003	- OSAC METAOS	US CONCERTINATION	CONCENTRATION
5.1			0.00			NO LAB	
<u> </u>			999			REPERT	
			() (2.0)			Kircki	
<u> </u>			0,0,0				
1							
ACD			999			 	
7 65							
BAS			000				
			 			 	}
						 	
			ļ				
							}
			<u> </u>				
				<u> </u>			<u> </u>
			<u> </u>			<u> </u>	
. FEEDSTOC	KS (See Appendix for CAS Mumbers.)	•				
CATEGORY	01 FEEDSTOCK		02 CAS NUMBER	CATEGORY	01 FEEDS	OCK NAME	02 CAS NUMBER
FOS				FDS			
FDS				FDS			
FDS			 	FDS			
FDS			 	FDS			
I SOUBCED	OF INFORMATION (CITO SOL	100 /010/00000 C P			 -		
	DIUR Lonsin						

SEPA

POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT SCRIPTION OF HAZARDOUS CONDITIONS AND INCIDE

I. IDENTIFICATION

OF STATE OF SITE NUMBER

OF TO TENTIFICATION

PART 3 - DESCRIPTION OF HAZARDOUS CONDITIONS AND INCIDENTS	1.0	212 [10] 1700
IL HAZARDOUS CONDITIONS AND INCIDENTS	/	
01 ☑ A. GROUNDWATER CONTAMINATION 02 ☐ OBSERVED (DATE) 03 POPULATION POTENTIALLY AFFECTED: 2014 NARRATIVE DESCRIPTION	Z POTENTIAL	☐ ALLEGED
There is high potential for groundwater. Contaminat	ion Since	the
discontinuous nature of Soil Strata	of the ir	rugular,
01 D B. SURFACE WATER CONTAMINATION 02 D OBSERVED (DATE:) 04 NARRATIVE DESCRIPTION	E POTENTIAL	☐ ALLEGED
There is a high potential for Surface Water Cont Surface whiter runoff from the landful site area	tamnation	Sincu
Surback whiter runoff from the landfill site area	blows int	to the
Rouge River located 800 - 1000 away		·
01 T. C. CONTAMINATION OF AIR 02 TO OBSERVED (DATE:) 03 POPULATION POTENTIALLY AFFECTED:04 NARRATIVE DESCRIPTION	☐ POTENTIAL	C ALLEGED
NA		
01 C D. FIRE/EXPLOSIVE CONDITIONS 02 C OBSERVED (DATE:)	POTENTIAL	☐ ALLEGED
03 POPULATION POTENTIALLY AFFECTED 04 NARRATIVE DESCRIPTION		
NIA	,	
-	<i>→</i>	
01 DE DIRECT CONTACT 03 POPULATION POTENTIALLY AFFECTED 1500 04 NARRATIVE DESCRIPTION	E POTENTIAL	C ALLEGED
There is petuntial for direct contact aspecially	by child	(ur)
Since the landful is the climentary School property	الان نهده	
not banced.		
01 9 F. CONTAMINATION OF SOIL 5 - 10 02 0 OBSERVED (DATE.) 03 AREA POTENTIALLY AFFECTED: (Acres) 04 NARRATIVE DESCRIPTION	POTENTIAL.	CALLEGED
There is pitential for Contamination of Soil 5	Since The	5.06
is most likely in purmuable strata		•
01 G. DRINKING WATER CONTAMINATION 02 COBSERVED (DATE 03 POPULATION POTENTIALLY AFFECTED 04 NARRATIVE DESCRIPTION	C POTENTIAL	ALLEGED
N/A		
<i>⊳</i> / <i>⊓</i> .		
01 TH. WORKER EXPOSURE/INJURY 02 TO OBSERVED (DATE:)	C POTENTIAL	_ ALLEGED
03 WORKERS POTENTIALLY AFFECTED: 04 NARRATIVE DESCRIPTION		
N/A	•	
01 ZI. POPULATION EXPOSURE/INJURY 1500 02 0 OBSERVED (DATE:	D POTENTIAL	ALLEGED
Since the site has high potential for surface	in water,	Sword
water, and Soil Contomnation, population exposure	. Could ba	very
extensive considering the immediate area is resident	Justial.	

& EPA

POTENTIAL HAZARDOUS WASTE SITE PRELIMINARY ASSESSMENT

I. IDENTIFICATION	4

PRELIMINANT ASSESSMEN	1 7 I
PART 3 - DESCRIPTION OF HAZARDOUS CONDITI	IONS AND INCIDENTS

O1 STATE 02 SITE NUMBER

PART 3 - DESCRIPTION	OF HAZARDOUS CONDITIONS AND INCID	ENTS TARE	1207431194452
II. HAZARDOUS CONDITIONS AND INCIDENTS (Contre	lued)		
01 GJ. DAMAGE TO FLORA 04 NARFATIVE DESCRIPTION	02 C OBSERVED (DATE:	_) @ POTENTIAL	☐ ALLEGED
Suffece wetter runder o	sold demage plane locate	d hutton	The
Site and the Resign			
01 CK. DAMAGE TO FAUNA 04 NARRATIVE DESCRIPTION (Include numbers) of appecies)	02 C OBSERVED (DATE:		C ALLEGED
boundary in which control	within 600' of the Edi	word Hinus P	Cark Oark
animals (raccons, operson	m, birds (ic.) as well as dig	s and cut a 6100	The resident
01 TL. CONTAMINATION OF FOOD CHAIN	02 C OBSERVED (DATE:	_) POTENTIAL	C ALLEGED
- The migration of Conta	minution into the long	Su River co	ાત
hemans	as fish from the river	are consume	d by
01 TM. UNSTABLE CONTAINMENT OF WASTES	02 - OBSERVED (DATE:	_) D'POTENTIAL	G ALLEGED
OS POPULATION POTENTALLY AFFECTED:	oble Containment of was	tes exists a	s the
landful was active pro	- To Act 87 when landfill	IS were not 1:	consul.
01 \$\infty\$ N. DAMAGE TO OFFSITE PROPERTY 04 NARRATIVE DESCRIPTION	02 C OBSERVED (DATE:	_ G-POTENTIAL	C ALLEGED
	be to offsite property	Exists prima	عہ.اب
for Edward Homes Park,	as it is topigmehoully	lawer than t	the S.Eu.
01 0. CONTAMINATION OF SEWERS, STORM DRAINS, 04 NARRATIVE DESCRIPTION	WWTPs 02 C OBSERVED (DATE:	_) TOTENTIAL	☐ ALLEGED
Sofue water rundly	Could flow into the res	idential Se	ww.5
and Contaminate the	e System.		
01 P. ILLEGAL/UNAUTHORIZED DUMPING 04 NARRATIVE DESCRIPTION	02 G OBSERVED (DATE:	_) □ POTENTIAL	☐ ALLEGED
• .	1110		
	MA		
OS DESCRIPTION OF ANY OTHER KNOWN, POTENTIAL (OR ALLEGED HAZARDS		
N	12		
IL TOTAL POPULATION POTENTIALLY AFFECTED:			
V. COMMENTS			
AIU	•		
- 111			
/. SOURCES OF INFORMATION (Cite apacific references, 6, 9,	, staro rives, samble analysis, reports)		
M DNR Lansing blus	E.P.D.		
MAYNE County Health	Department		
, , , , , , , , , , , , , , , , , , , ,	· · · · · · ·		

SED 301-A0101

Grgh- Byll 1/31/89

Site Name and Location

Cooper School 28611 Ann Arbor Trail Westland, MI 48185 County: Wayne

Michigan Code Number: 82-02S-09E-01CB

DNR District: Detroit

EPA ID Number: MID981189905

SAS Score/Screen No.: 02

The Cooper School site was an active municipal waste landfill from approximately 1925 to 1952. According to the Wayne County Health Department records, the types and amounts of municipal waste deposited in the landfill are unknown as well as its size.

The landfill, located on Cooper Elementary School property, is unfenced, and adjacent to a highly populated residential area and public park. The Rouge River, located approximately 800 feet from the site, flows through the park and lends itself to potential contamination through surface water runoff should the landfill be leaking.

The drinking water for residents within a three mile radius of the site is derived from Detroit's municipal water system, and is not threatened by the presence of the landfill.

No testing of water or soil has been conducted, and it is not known whether or not leachate from the landfill is present. The potential for such leachate is high as the site was active prior to Act 87, requiring the licensing of landfills.

Further research and preliminary water and soil testing is recommended as this landfill has the potential of endangering approximately four hundred children attending the school, as well as nearly 100,000 residents in the surrounding area.

Recommendations for EPA

This site receives a high priority for inspection

Pre-HRS Score: To be determined

Projected HRS Score: To be determined

SI Priority: High - State lead

Hours Spent: 10 10 + 5 + + + = 10.5

Initial & Date: 10 11-10-67 5.C.

Date of Previous Summary: Previous Author: Current Date: 11-12-37

Author: Debra Spakoff

Site Assessment Unit Environmental Response Division Michigan Dept. of Natural Resources

Ref # Site Name Cooper MID # 981184903

> soper School County

CALL LOG

Verify Site Location and Size.

Verify # and size of each containment structure.

Is there existing exposure of people documented? Is the site fenced? Is it secure?

If sampling was done, how were samples collected? i.e. random selective,

Has the fire marshall considered the site a fire hazard? What type of companies used the site? (Origin of chemicals)

DATE

3-13-38

LVonia City Hall

Water Service Dept. (3,3) 421-2000

PHONE NUMBER PERSON CONTACTED

D. wow

Tom moore The Sw part of Liveria (5 of phymouth Rd a w of wayne) has a few homes that use groundwater for impation. Savend vasidents near Newborgh lake use groundence for driveng

2-17-88

2:00 pm

Livonia City Hall

Water Service Dept.

B13) 4212000

Tom Movie W.C. H.D issues well parmits and so a Barbera Branc will call to give me a lost of these perhones. (326-4900) Permit Dept (729-2211)

Tom will send me a list of homes with selver only service. This excludes those people with private water & Swar as well as those who have a well for instation purposes in addition to their City water Supply.

2-26-88 westland water Dept. (3,3)467-3,735

Arthor table. Tala

Superintendent of the water Division 5.45pm Homes recieving swar only service are gooding Their water from adjacent CITIES Mr Witale is not a ware of anyong who is using groundwater for drinking purposes However to Knows to 3-4 homes which use groundwater occessmally for watern's they laws in the Summer Location of the homes is part known. Prepared by: Weban A Shak

Site Name	Cooper School	
County	Wayna	

CALL LOG

1) Verify Site Location and Size.

2) Verify # and size of each containment structure.

Is there existing exposure of people documented?

4) Is the site fenced? Is it secure?

5) If sampling was done, how were samples collected? i.e. random selective, surface grab, composite etc..

6) Has the fire marshall considered the site a fire hazard?

7) What type of companies used the site? (Origin of chemicals)

DATE

AGENCY

PHONE NUMBER PERSON CONTACTED

10-28-87 Wayne Co Health Dept. (313)326-4900 Bob Ratz

The Site was an active municipal waster lands III between 1925 + 1952 (approx desert). The exact Siteh and types of waster is not known. An wementary school has been built adjacent to the site.

The Site is unferced.

No testing has been done.



WAYNE COUNTY **DEPARTMENT OF HEALTH**

ENVIRONMENTAL HEALTH DIVISION

VERNICE-DAVIS-ANTHONY, MPH Health Officer

DONALD LAWRENCHUK, M.D., MPH Medical Director

3669 METRO PLACE MALL WAYNE, MICHIGAN 48184 Telephone: (313) 326-4900

October 1, 1984

KEUEINER CCT 1903

Site Name MID # 9811

Mr. Lonnie Lee DNR - Remedial Actions Stevens T. Mason Bldg. P. O. Box 30028 Lansing, Michigan 48909

Dear Mr. Lee:

Re: Landfill Sites for Evaluation Under Act 307

Enclosed is information on seven (7) old landfills within Wayne County. Two (2) of these landfills are already on the Act 307 priority list, however, some of the provided information may be new. The other five (5) sites are landfills that this department has some concerns over and thought they should be evaluated and scored by your group. The sites are:

- Satterlee Hard Fill Sumpter Twp. (previously scored)
 - Satterlee Dump #2 Romulus (Dump near Wicks Elementary School previously scored)
 - 3. Mendrick's Romulus (Located adjacent to and north of Satterlee Dump #2)
 - 4. Cooper School site Livonia
 - 5. National Airport site Westland
 - 6. Dial Trucking Plymouth
 - 7. Erving Brown Flat Rock

The information enclosed is somewhat sketchy for some sites, however, it is the best available. If you have any questions please contact me at (313) 326-4900. ext. 70.

Very truly fours

Public Health Engineer

RNR:1s

Enclosures

200	Cosper Core 20011 Fine Open	
Cath	Elementary 5.06 AH. Trail	UCHD 612 326-4900
	SITE NAME COOPER School SITE (•
	SITE LOCATION	725 RGE Sect 444 344
	SITE SIZE & 5-10 ACRES	Carolina (20)
•	EXPOSSIZE POTENTIAL SITE IS LOCATED NE	. · · · · · · · · · · · · · · · · · · ·
<i></i>	-ENCING SECURE NO FENCINE	NOT SECURE
	HIMPLING DATA NONE	
	FIRE HAZARD NONE	
V	VASTE TYPES + COMPANIES MUNICIPAL	- WASTE
; *		
\rightarrow \leq	SITE NAME REDFORD TWP #1 D	ump
4	SITE LOCATION	TIS RIVE SEC 29 SW4
	SITE SIZE	
	EXPOSURE POTENTIAL NO PROBLEMS	S EUFOENT
	FENUNG, SELURE FENCING	up but site not secure
	SAMPLUL DATA NONE	
	FIRE HAZARD NONE	
	WHOTE TYPES + COMPHUES MU	DUICIPAL Suspected
tions the second se		
the state of the s		
	SITE NAME REDFORD TWP #2	Dump
	SITE LOCATION	TIS RIVE SELLO N'Z SE 4
·	SITE SIZE Redoc Steel	House restaurant Located on site
	EXPOSURE POTENTIAL GAS VENTING	
·	FENCING SECURE SITE A	OT SECURE
	SAMPLING DATA NONE	
	FIRE HAZARD	
	WHSTE TYPES TLEMPANIES MODE	CIPAC
	11	•

MICHIGAN

Ground-Water Resources

Ref # 7
Site Name Cospar School
MID # 98 11849 0 5

Ground water is the source of 17 percent of public-water supplies and nearly 100 percent of the domestic-water supplies in Michigan (Bedell, 1982). Ground water supplies 43 percent of the State's population; however, ground water accounts for only 4 percent of the total water used in the State because most supplies for large urban areas are from surface water, particularly the Great Lakes (Solley and others, 1983; Weist, 1978). Distant from the Great Lakes, water supplies generally are obtained from ground water. Ground-water withdrawal for irrigation is about 37 percent of the total water used for irrigation (Bedell and VanTil, 1979; Solley and others, 1983). Ground-water withdrawals in 1980 for various uses, and related statistics, are given in table 1.

Chemical characteristics of natural ground water in Michigan are determined primarily by the geologic environment through which the water flows. Natural ground water generally is suitable for human consumption and most other uses. Water from glacial deposits, at places, contains large concentrations of iron [2.5-5.0 milligrams per liter (mg/L)]; water from carbonate rocks is likely to be very hard (400-900 mg/L as calcium carbonate); and water from the Saginaw aquifer in the Saginaw Bay-Thumb area commonly is very mineralized (2,000-80,000 mg/L of dissolved solids). Throughout the State, salty water underlies freshwater at depths ranging from about 100 ft in the eastern part of the Lower Peninsula to about 900 ft in the northern part. Average dissolved-solids concentration of water from bedrock (535 mg/L) is about twice as great as the average concentration from glacial deposits (241 mg/L) (Cummings, 1980).

Michigan has identified more than 1,000 sites where ground water has been contaminated to some degree and an even greater number of sites where pollution is suspected (Michigan Department of Natural Resources, 1985). A wide range of contaminants is involved. At many sites, chlorinated hydrocarbons and hydrocarbons that are contained in fuel substances are the contaminants. Nitrates from surface sources have contaminated domestic ground-water supplies in concentrations of as much as 30 mg/L at some locations in the Lower Peninsula (Cummings and others, 1984).

GENERAL SETTING

Michigan is divided into two principal physiographic provinces. The Lower Peninsula and the eastern part of the Upper Peninsula of Michigan are in the Central Lowland physiographic province. These areas are underlain by layered sedimentary bedrock of Paleozoic and Mesozoic age. The western part of the Upper Peninsula is a part of the Superior Upland physiographic province, which is underlain by igneous, metamorphic, and sedimentary rocks of Precambrian age. Glacial deposits cover most of the State.

Glacial deposits consist of sand, gravel, silt, clay, and boulders. Sand and gravel, such as in outwash and glaciofluvial deposits, are productive aquifers; mixtures of clay, silt, sand, gravel, and boulders, which form some till deposits,

Table 1. Ground-water facts for Michigan

[Withdrawal data rounded to two significant figures and may not add to totals because of independent rounding. Mgal/d = million gallons per day; gal/d = gallons per day. Source: Solley, Chase, and Mann, 1983]

•	
Population served by ground water, 1980	
Number (thousands)	3,978
Percentage of total population	4
Number (thousands)	1.316
Percentage of total population	14
T	-
Number (thousands)	2.66
Percentage of total population	2
Freshwater withdrawals, 1980	
Surface water and ground water, total (Mgal/d)	15,00
Ground water only (Mgal/d)	530
Ground water only (Mgal/d) Percentage of total	4
Percentage of total excluding withdrawals for	
thermoelectric power	1
Category of use	
Public-supply withdrawals:	
Ground water (Mgal/d)	- 22
Ground water (Mgal/d)	- 4
Percentage of total public supply	- 1
Per capita (gal/d)	- 16
Rural-supply withdrawals:	
Domestic:	
Ground water (Mgal/d)	- 16
Percentage of total ground water	- 3
Percentage of total rural domestic	- 10
Per capita (gal/d)	- 6
Livestock:	
Ground water (Mgal/d)	- 1
Percentage of total ground water	-
Percentage of total ground water Percentage of total livestock	- 7
Industrial self-supplied withdrawals:	
Ground water (Mgal/d)	- 6
Percentage of total ground water	- 1
Percentage of total industrial self-supplied:	
Including withdrawals for thermoelectric power	-
Excluding withdrawals for thermoelectric power	-
rrigation withdrawals:	
Ground water (Mgal/d)	- 7
Percentage of total ground water	- 1
Percentage of total irrigation	- <u>3</u>

generally are poor aquifers. Lacustrine deposits that are predominantly sand are productive aquifers; those that are predominantly clay yield little or no water. In the northern part of the Lower Peninsula, glacial deposits in some areas are more than 800 feet (ft) thick; in most other areas in the State, the deposits are less than 200 ft thick.

In the Lower Peninsula and eastern Upper Peninsula, bedrock, which underlies glacial deposits and crops out at a few places, consists principally of Paleozoic shale, limestone, and sandstone. These rocks have been deformed into a structural feature known as the Michigan basin (Newcombe, 1933). Sandstone and limestone are productive aquifers and, where near enough to land surface to be recharged by precipi-








Figure 1. Principal aquifers in Michigan. A, Geographic distribution. B, Physiographic diagram and divisions. C, Generalized cross section (A-A'). (See table 2 for more detailed description of aquifers. Sources: A, Farrand, 1982. B, Martin, 1936; Raisz, 1954. C, Compi led by N. G. Grannemann from U.S. Geological Survey files.)









		lic supply]
No. on map	Geographic area	Aquifer
1	Lansing, East Lansing,	Saginaw Formation,
	Michigan State University.	glacial deposits.
2	Kalamazoo	Glacial deposits.
2 3	Battle Creek	Marshall Formation.
4	Jackson,	Saginaw and Marshall Formations.
5	Waterford Township	Glacial deposits.
6	Ypsilanti, Ypsilanti Township.	Do.
7 8	Coldwater	Do.
8	Albion	Marshall Formation.

Figure 2. Areal distribution of major ground-water withdrawals and graphs of annual greatest depth to water in selected wells in Michigan. (Sources: Withdrawal data from Bedell, 1982; water-level data from U.S. Geological Survey files.)

		WATER V			· 1	MICHIGAN DEPA	ARTMENT
LOCATION OF WELL		AC 1 23-				PUBLIC HEA	LTH
County	Fownship Name		Fraction		Section Number		Range Number
Wayne	Dearborn He	zights	1/4	1/4 1/4	9	2 X/s.	DEX
Distance And Direction from Ros Carriage Park	Apts. SE Con	mer of]		3 OWNER OF	Carria	ge Hill Api	
8514 Inkster Ro		ny Rd.		Address	-	est Maple	
Street address & City of Well Lo						Mi 48084	
Locate with "X" in section b		n Map:				Date of Completion	n ¯ ˙
	₩e	11 #7		<u>81</u>		May 15, 82	1
				5 Cable to		=	
w				6 USE:		ed Bored	
						Conditioning	
			:	□Tes			
				7 CASING: TH	readed Welde	d Height: Ab	ove/Below
1 MILE				1		Surface	
2 FORMAT	ION	THICKNESS OF	DEPTH TO BOTTOM OF		_69_ft. Dept		
		STRATUM	STRATUM			th Drive Shoe	? Yes X No
Top Soil		1 3	3	8 SCREEN:			
100 0011					<u>w/w</u>		
Black Clay		5	8 .		ft. and _	-	
				Fittings:			
Gray Clay		4	12				
	_	_		9 STATIC WAT			-
Gray clay grave	1	3	<u> 15 </u>		ft. below land su EVEL below land		
a		AE	50			pumping	
Gray Clay		45					
Gray Clay & Gra	wel	26	76	l	ft. efter hrs.	pumping	g.p.m.
——————————————————————————————————————			\	11 WATER QUA	ALITY in Parts Per	Million:	
Sand & Gravel		5	81	Iron (Fe) _	Chic	rides (CI)	
				1			
					COMPLETION:	In Approved P	
				1		12" Above G	
	<u> </u>		 		ed? Yes No		
	•	Į,			ement Bento		
			-		omft.		
		ļ			urce of possible o		
					Direct		Туре
				Well disinfo		etion Yes	No
						Not installed	
<u> </u>					er's Name ber	HP Vol	
	·		<u> </u>	,		t. capacity(
				1	Submersible		
		ļ	<u> </u>	1 0	Jet	Reciprocating	
USE A 2ND SHEET 16 Remarks, elevation, source		L	17 WATER	WELL CONTRA	CTOR'S CERTIF	ICATION!	
	•		This wel	I was drilled u	nder my jurisdicti	on and this report	is true
DHY HOLE = WON	TOPPIND WATER.	tem NUL		· ·	edge and belief.	,	0026
	*CORRECTED BY	/	REGI	STERED BUSINES	ing Co. Inc	REGISTE	RATION NO.
'	**ADDITION BY		Address	Howel	<u> </u>	48843	
	ELEVATION		_	¬ /	00	4004)	
	DEPTH TO ROCK	35	Signed	AUTHORIZED BE	PRESENTATIVE		
D67d 100M (Rev. 12-68	3)			AUTHORIZED E	TALIBLES		

AUUIU	5 ८		
			ORD MICHIGAN DEPARTMENT
1 LOCATION OF WELL	ACT 29	4 PA 196	OF PUBLIC HEALTH
County Township Name		Fraction	Section Number Town Number Range Number
Wayne Dearborn	Height	5 1/4	14 14 6 2 NS. 10 EVIK
Distance And Direction from Road Intersections	4		3 OWNER OF WELL: Carriage Hill Apt. Co.
	omer of I	nketer	Address 2900 West Maple
Street Dearborn Herethiseation	oh we		Troy, Mi 48084
	tch Map:		4 WELL DEPTH: (completed) Date of Completion
¥	e11 #6	i	156 tt. May 4, 82
├ 			5 Cable tool Rotary Driven Dug
wL			Hollow rod Jetted Bored
			6 USE: Domestic Public Supply Industry Irrigation
			Test Well
			7 CASING: Threaded Welded Height: Above/Below-
1 MILE	T		Surfaceft.
2 FORMATION	THICKNESS OF STRATUM	DEPTH TO BOTTOM OF	_5_in. to 105ft. Depth Weightlbs. ft.
	STRATUM	STRATUM	in, toft. Depth Drive Shoe? Yes No No
Brown Clay	10	10	Type: Dia.:
			Slot/Gauze Length
Gray Clay	36	46_	Set between ft. and ft.
		40	Fittings:
Gray Clay & Fine Gravel	2	48	9 STATIC WATER LEVEL
Grav Clav	91	57 1	9 ft. below land surface
			10 PUMPING LEVEL below land surface
Fine Gravel & Stone	21/2	60	ft. after hrs. pumping g.p.m.
	,,	TTE	ft. after hrs. pumping g.p.m.
Gray Clay	15	13	11 WATER QUALITY in Parts Per Million:
Black & Brown Limestone Oily	5	80	Iron (Fe) Chlorides (CI)
		م دو	
White & Brown Limestone		. 95	12 WELL HEAD COMPLETION: In Approved Pit
		~	Pitless Adapter 12" Above Grade
Brown Limestone	2	97	13 Well Grouted? Yes No
Crev Limestone	8	105	Neat Cement Bentonite
		/ \	Depth: Fromft. toft.
Gray Idmestone w/Shale Ienses	5	/110/	14 Nearest Source of possible contamination
		\	Type Well disinfected upon completion Yes No
Gray Shale and Gray Idmestone	6/	116	\\ 5 PUMP: \Box Not installed
Gray Brown Linestone	40	156	Manufacturer's Name
	/		Model Number HP Volts
<u></u>	1	<u> </u>	Length of Drop Pipeft. capacityG.P.M.
	1		Type: Submersible
<u> </u>			Jet Reciprocating
USE A 2ND SHEET IF NEEDED			
16 Remarks, elevation, source of data, etc.			WELL CONTRACTOR'S CERTIFICATION: I was drilled under my jurisdiction and this report is true
DRY HOLE - WOM'T PULP WATER		to the b	est of my knowledge and belief.
AUDED INFO BY DRILLER, IIEM B	W C.	- REGI	STERED BUSINESS NAME REGISTRATION NO.
*CORRECTED BY		ļ	
**ADDITION BY ELEVATION			Howell , 111 48843
DEPTH TO ROCK		Signed	AUTHORIZED PEPRESENTATIVE
D67d 100M (Rev. 12-68)	مُختَدُ	-	AUTHORIZED PEPRESENTATIVE

6-4-16-156

WATER WELL RECORD

MICHIGAN DEPARTMENT

1 LOCATION OF WELL	ACT 294	PA 196	.		OF PUBLIC HEA	LTH
County Township Name	li li	Fraction		Section Number	Town Number	
Wayne & Decripsin	팬 .	. 1/4	14 14	l 1.	2 x/s.	
Distance And Direction from Road Intersections	FREN	<u> </u>	3 OWNER OF		<u> </u>	1000
Carriage Park Arts. SE Corner	Of Inkste	r end			ge Hill Apt	:- Co-
8514 Inkster Joy Rd	is.		Address	2900 W	est Maple	
Dearhorn Heights Nich.	D14- 40		l		%i 48084	
Stree Dearborn, Heights Lich. Locate with "X" in section below Sket	BTOR® AS		4 WELL DEPTH		Date of Completion	
						
Well	# フ				April 2, 8	
			5 Cable to		=	= '
W E			Hollow		ed Borec	
			6 USE: Dor		ic Supply	
			_ =	=	Conditioning [] Commercial
			Tes			
 			Diam.	readed Welde	Height: Abo	
1 MILE	Time varies	OFRICE TO			Surface	
2 FORMATION	THICKNESS OF	DEPTH TO BOTTOM OF		107ft, Dept	•	
	STRATUM	STRATUM	in. to	ft. Dept	h Drive Shoe	Yes X No
	3.	1.	8 SCREEN:	RUCK		
Top Soil	1.0	호!	Type:	<u></u>	_ Dia.:	····
			Stot/Gauze		_ Length	· · · · · · · · · · · · · · · · · · ·
Brown Clay	142	15	Set between	ft. and _	ft.	
			Fittings:			
Gray Clay	30	45			.	
	1		9 STATIC WAT	ER LEVEL		
Gray Clay & Gravel	31	76		ft. below land su		<u>.</u>
			10 PUMPING I	EVEL below land	surface	
Gray Clay & Cobbles w/Occ. Boul	der 23	99	ļ ——	ft. after hrs.	pumping	g.p.m.
	1		i			
Brown Limestone	2	101		ft. after hrs.	pumping	g.p.m.
			11 WATER QU	ALITY in Parts Per	Million:	
Boulders & Cobblestone	3	104	Iron (Fe) _	Chic	rides (CI)	
200250		<u> </u>	ļ			
Hard Grey Shale	13	117	Hardness	Othe	r	
ZZIZW GZ G			12 WELL HEAD	COMPLETION:	In Approved P	rit
Crayioh-Black Shale	3	128			12" Above Gr	ade
		, 32.0	13 Well Grout	ed? 🔲 Yes 📗 No)	
Cross Shale	9	129		ement 🔲 Bento		
TA DIRECT			Depth: Fr	omft.	toft.	
PRess Chale	2	131	14 Nearest So	urce of possible o	contamination	
BRown Shale			fee	t Direct	ion	Түре
Soft Med Gray Shale	2	133	Well disinf	ected upon compl	etion 🗌 Yes 🔲 I	No
			15 PUMP:	<u> </u>	Not installed	
Lime Stone	<i>8</i> 7	220	Manufactu	rer's Name		
		· · · · ·	3		HP Vol	ts _
Gray Shale	5C	270			t. capacity(
	 		l	Submersible	======	
Lime Stone	45 /	315	=	Jet	Reciprocating	
	60		1 "	J-1		
Sandstone	00	375 378				
16 Remarks, elevation, source of data, etc.			WELL CONTRA	ACTOR'S CERTIF	ICATION:	
To the state of th		This we	II was drilled u	nder my jurisdicti	on and this report	is true
				ledge and belief.	_	
DRY HOLE - WON'T MAKE OR TAKE		REG	SPERED DOSINE	Ling Co. II	REGIST	APION NO.
AODED INFO BY DRILLES	R, ITEM NO.					
*CORRECTED BY		Address	- Howe	11 , 14 -	48842	
**ADDITION BY	•		7 1-	DR	·	
ELEVATION		j Signedy	AUTHORIZED	PRESENTATIVE	Date	· · · · · · · · · · · · · · · · · · ·
D67d 100M (Rev. 12-68) DEPTH TO ROCK	C 4.			_		

GEOLOGICAL SURVEY ACT	29 1981WATER	WELL /	AND PL	JMP RE	Ref.# Site Nam	<u>2</u> e C50 pu	r School
1 LOCATION OF WELL	·		ACT 368. P.A		MID # 9	31189905	
County Wayne	Township Name Dearborn leight	ts	Fraction 1/4	1/4 1/4	ection Number	Town Number	Range Number
Distance And Direction From Road	d intersection			3 OWNER OF W	ELL:		
700' S.E. of Inkster & Joy Road Carriage Park Apartments 8640 Canfield, Dearborn Heights 48127			Carriage Hill Apartments Co. 2900 W. Maple Road Address Some As Well Cocaron Hichigan 48084				
Locate with X in Section Below	Sk	etch Map.		4 WELL DEPTH		Date of Compile	1
W				Cable toot Hollow rod G USE Domes Irr.gatic	Rótar Auge tic Type Type Aell Type	Jetted † Public [Dug Type iii Public Heat sump
1 MILE				Diameter SA 9	fastic Weld	ed Surface	_ 1
2 FORMATION D	ESCRIPTION	THICKNESS OF STRATUM	DEPTH TO BOTTOM OF STRATUM	in. to _	92 ft. depth ft. depth		II tes /ft.
				6 3/4 in to	92ft. depth	Drive Shoe	Yes Yes
Fill sand and gr	avel	10'	10	SCREBN	ft. depth		
Clay (gray)		401	50			Diameter	nstalled
Heavy gravel wit	h clav	21	52				
	•	11'	63	FITTINGS:	K-Packer	Lead Packer	
Sharp, firm medi	•			9 STATIC WATER	LEVEL		0 -
Medium and fine	waterground	5'	68	10 PUMPING LEVI	ft. below land s EL: below land s		How
Gray clay with s	ome gravel	7'	75		•	pumping at6	- 1
Layered sharp gr	avel and watersam	1 15'	90	11 WELL HEAD	Pitless a	dapter V 12	above grade
Limestone		47'	137	COMPLETION	=	7	proved p.t
Sable and limest	one/mived)	58'	195	12 WELL GROUTE	D? No	Yes From	0 to 92 f t.
Juile and Timest	aile/intxea)			☐ Neat ceme	ent 🙀 Bent	onite 🔲 Other	
Sandstane and gr	ay shale	125'	320	No. of bags of	cement		
Sandstone	······································	61'	381	Type _C+n=	m Pradir ^D ista	ince <u>50 ft.</u> Di	ection ection
Gray Shale		31	384			n?	
				14 PUMP	Not installed	Pump In	stallation Only
Salt		19'	403]	name		
	HESC BY DRILLER, ITEM NO.			1			Volts G P M.
•	TIED BY				Submersible	Jet	1
ELEYAT	ION			•			
use A APSHE	- 40-47-	1	16 14/475	Model number R WELL CONTRA		Capacity	Gaitons
2" opening in be oil at 114' 381' - 403' Blac	_	e	This we to the t	ell was drilled under best of my knowledg	my jurisdiction a je and belief.	nd this report is tru	
			Signed	- Trans	O REPHESENHA N	Marie	1/4/82
D67d (Rev. 10-8	0)			- AUTHORIZE	O METHEDENHA NY	_	, · · ·

• • • • • • • • • • • • • • • • • • • •			
'AUG 1 6 1982	WATER V		
1 LOCATION OF WELL	ACT 29		PUBLIC HEALTH
County Township Name	jų ,	Fraction	Section Number Town Number Range Number
Wayne Decroom He Distance And Direction from Road Intersections	olghis.	1 1/4	1/4 1/4 0 2 A/S. 10 E/S.
	mer of :		Carriage Hill Apt. Co.
8514 Inkster Rd. and Jo			Address 2900 Wast Maple
Street Dearborn, Heightstion			Troy, M1 48084
Locate with "X" in section below Sketch			4 WELL DEPTH: (completed) Date of Completion
Well	#8		159 ft. May 27, 82
			5 Cable tool Rotary Driven Dug Hollow rod Jetted Bored
│ ₩ ├ - ┥── ╡── ┤── ┤──			6 USE: Domestic Public Supply Industry
	•		Irrigation 🔀 Air Conditioning 🔲 Commercial
			Test Well
1 MILE			7 CASING: Threaded Welded Height: Above/Below Diam. Surfaceft.
	THICKNESS	DEPTH TO BOTTOM OF	
2 FORMATION	STRATUM	STRATUM	in. toft. Depth Drive Shoe? Yes 🗖 No 🗌
			8 SCREEN: Rock Well
Black Top soil	2	2	Type: Dia.:
_ Brown Clay	7	9	Stot/Gauze Langth ft.
			Fittings:
Gray Clay	61	70	Domano ware a five
	~~	~7	9 STATIC WATER LEVEL
Gray Clay and Bolders	27	97	ft. below land surface
Limestone Brown	23	120	
- 111 - 111 - 11			150 14 75
Gray Shale	6	126	11 WATER QUALITY in Parts Per Million:
Brown Idmestone	74	140	Iron (Fe) Chlorides (CI)
Fine Shale	19	159	12 WELL HEAD COMPLETION: In Approved Pit
			Pitless Adapter 12" Above Grade
			13 Well Grouted? Yes No
			Neat Cement Bentonite
			Depth: Fromft. toft.
			14 Nearest Source of possible contaminationfeet Direction Type
			Well disinfected upon completion Yes No
			15 PUMP: Not installed
			Manufacturer's Name
ADDED INFO BY DRILLER, ITEM &	o.		Model Number HP Volts
*CORRECTED 8Y	<u> </u>		Length of Drop Pipeft. capacityG.P.M. Type: Submersible
P * ADDITION BY ELEVATION	:		Jet Reciprocating
DEPTH TO ROCK			
16 Remarks, elevation, source of data, etc.	L. <u>.</u>	17 WATED	WELL CONTRACTOR'S CERTIFICATION:
Homeling, elevation, source of data, etc.		This wel	I was drilled under my jurisdiction and this report is true
This Well pumps Healy good		to the be	IST of my knowledge and belief. STERED BUSINESS EMPO INC. REGISTRATION NO.
		Add	
		Address	Howell , 14 48843
<u></u>	·	Signed	Source Brandate
D67d 100M (Rev. 12-68)			AUTHORIZED REPRESENTATIVE

Mayne Dearborn Heights ance And Direction From Road Intersection OFL. S. E. of Inkster & Joy Road Intersection OFL S. E. of Inkster & Joy Road Intersection	s	1/4	3 OWNER OF WELL: Carriage Park Apartments Address 2900 W. Maple Road Troy, MI 48084 Address Same As Well Location? Yes No 4 WELL DEPTH (completed) Date of Completion 92 ft. Date of Completion 92 ft. Driven Dug
10 Ft. S. E. of Inkster & Joy Road Arriage Park Apartments 140 Canfield, Dearborn Heights, MI 15te Address & City of Well Location 15te with IX in Section Below Sk			Carriage Park Apartments Address 2900 W. Maple Road Troy, MI 48084 Address Same As Well Location?
ste with "X" in Section Below Sk	etch Map		4 WELL DEPTH: (completed) Date of Completion
	eich Map		92 ft. 11/21/8] ⁵ ☐ Cable tool ☐ Rotary ☐ Driven ☐ Dug
1 MILE			6 USE: Domestic Type Public Type III Public
	1		Irrigation
FORMATION DESCRIPTION	THICKNESS OF STRATUM	DEPTH TO BOTTOM OF STRATUM	in, toft, depthin toft. depthft. depthin toft. depthft. depth
11 Sand Gravel	10'	10'	in, toft_ depth No
ay (grey)	401	50'	8 SCREEN: Type Johnson Stainless 4"
avy Gravel w/Clay	21	52 ⁴	Slot/Gauze 25-25-25-35
arp Medium Gravel	11'	63'	Blank above screen 2 ft. Other 68-75 Blank 9 STATIC WATER LEVEL:
dium & Fine Water Gravel	5'	681	ft. below land surface
ay w/Some Gravel	7'	75'	10 PUMPING LEVEL: below land surface 60 ft. after 8 hrs. pumping at 10 G.P.M.
reaks Sharp Gravel, Water Sand	17'	92'	60 ft. after 10 hrs. pumping at 15 G.P.M.
ack Shale, Sandstone, Hed. Gravel			11 WELL HEAD Pitless adapter
Salder at 80' & 91')			Neat cement Bentonite Other
			13 Nearest source of possible contamination Type Storm Nrain Distance 75 ft. Direction S.W.S.
s Encountered about 53' to about			Well disinfected upon completion? Yes No 14 PUMP: Not Installed Pump installation Only
<u>'')</u>			Manufacturer's name
-			Length of Drop Pipeft. capacity G.P.N TYPE: Submersible Jet PRESSURE TANK:
			Manufacturer's name
Remarks, elevation, source of data, etc. creen positions - 2' blank, 5' 25	slot	This we	Model number Capacity Gallor R WELL CONTRACTOR'S CERTIFICATION: Il was drilled under my jurisdiction and this report is true
blank, 2'-4' 25 slot, 2'-5' 35 soump cavitates at]5 gpm.)		j	est of my knowledge and belief. SUITIVAN Well Drilling 63-1790 REGISTERED BUSINESS NAME REGISTRATION NO.

32-15-9E Liwonia Twp. (Hayne Co.)

Peake Petroleum Company

Wayne County Boad Countsaton No. 3	Pormit 1	Permit No. 23362
Intilling Contractors B. G. Hilliard (Rotary) Location: NW\$ NW\$ Section 32, T. 15., R. 9E. 370' from North and 305' from West line of quarter section	etten	:
Herations 654.4 feet above sea level (rot. bash.)		
Record by: B. L. Champion from geologic log submitted by the co	Auschern	;
SHE :	Thickness (feet)	Copth (feet)
Print.	217	
MISSISSIPPIAN-DEVONIAN: Antrim-Treverse Formetion (1): Shale, "Antrim"	118	232
IEVONIAN: Traverse Limestone: Dolomita, 11cht brown, medium coarse	ន	245
	มหกา	% % % % %
Shale, gray Shale, gray Shale, gray	,3°°£	r R R R R R R R R R R R R R R R R R R R
Shale and limestone Shale, gray	ૢઌૢૺ ૽ઌૡૢ૽ૺ	1
Dundee: Limestone, light browr Dolomite, light brown, finely crystalline, limy	ક્ષ્ય ફ્રિ	25.5 25.5 25.5 25.5 25.5 25.5 25.5 25.5
light buff, very very fillight brown, very finely light gray, anhydritto very very finely orystalight brown, finely crys	ድድድያ	2000 2000 2000 2000 2000 2000 2000 200
Dolomite, gray brown, very ilnely crystalline Anhydrite Dolomite and anhydrite Dolomite, light brown, finely erystalline	۲-00 - ^{ال}	38 %§

Page 2-	H. R.	Ford Hell-Dearborn	Heyne	County)
---------	-------	--------------------	-------	---------

rage 2- h. M. Ford Mail-Deardorn (wayne County)	Thickness (feet)	Depth (feet)
Sylvania:	•	
Very porous and sandy dark buff gray bituminous and		. .
granular dolomite. Pure white quartz grains		
embedded in a matrix of dolomite.	10	505
Grayish to pure white fine grained sandstone, littl	-	
oemented. Glass sand	50	55 5
Grayish white colomitic sandstone	15	570
Hard very dolomitic gray sandstone and very sandy	10	
dolomite	10 •	EOA:
	5	580
Pure white fine grained sandstone-glass/sand	5	585
Gray to dark gray sandy to very sandy dolomite and	15	700
pure white and gray dolomitic sandstone	15	600
White to pure white sandstone grading downward into		
gray sandstone	20	620
Silurian:		
Bass Island:		
Rasin River Dolomite Member:	•	•
Gray to dark gray dense grained dolomite with much		
chert and some anhydrite	45	665
Light to dark buff and gray dolomite in places very	,	
argillaceous and some streaks of anhydrite	30	695
Light to very light gray and buff fine grained dolo	- 	•
mite, porous and colitic from 715-720 feet.	:	•
very cherty from 720-725 feet; and locally		
bituminous. Some streaks of anhydrite.	45	740
Dark buff, bituminous and laminated finely granular		1 20
dolomite	5	745
Gray to light grayish and buff dolomite and colite		, , , ,
with bituminous laminac	20	765
	حد الع	700
Bluish gray argillaceous dolomite with bluish		
mottlings and streaks, and very light buff to		
dark buff or brown bituminous and laminated		
dolomite, and some gray shale near the bottom	10	775
Light grayish buff dolomitc	15	790
Light buff gray mottled and streaked dolomite, coli	.to	10.99
at the top and gray to bluish gray laminated		U SS
bituminous and very argillaceous dolomite town	ird (•
the bottom	20	810
Vory light to light grayish buff dolomite, locally		
very argillaceous and with much white and gray	r .	
anhydrite, especially below 820 feet.	3 5	845
Blue and buff argillaceous delomite at the top; wit		***
pure white snhydrite at the bottom	5	850
Chiefly pure white anhydrite with some buff laminat		000
dolomito	5	855
	5	500
Dark buff, gray and black dolomite in places very		
argillacoous and bituminous, and ith a thin b		
of colite below 855 feet. Some anhydrite in a	•	
and in cavities	50	885
Light buff gray anhydrite and dolomite	20	905
Tymochtec Member:		
Grayish buff to dark gray very argillaceous dolomit	ic,	
blue gray and buff shale, colestite, ahhydrite		940
Rod shaly dolomite; soft gray and red shale	15	955
Chiefly dark gray shale and shaly dolomite	35	990